



LEGACY[®]



FLEXOR[™] POLYMER MODIFIED
ARCHITECTURAL SHINGLES

Distributed from:



Shown in:
Black Oak



LEGACY[®]



FLEXOR[™] POLYMER MODIFIED ASPHALT

Asphalt technology increases flexibility, granule adhesion, and impact resistance.



PROTECT FROM EXTREME WEATHER

Class 4 impact resistance offers your roof the highest rated protection available.



SCOTCHGARD[™] PROTECTOR: HELP PREVENT BLACK STREAKS

Resists algae staining and helps maintain the aesthetic appearance of your roof. Includes a Limited Lifetime Warranty.



RETAIN COLOR GRANULES

Superior granule adhesion provides your roof lasting beauty and protection from damaging solar rays.



FORMULATED ROOFING SEALANTS

Specially formulated asphalt sealant holds shingles in place during high winds and rain sealants protect from wind-driven rain.



SUPERIOR SHINGLE STRENGTH

Shingles with Flexor[™] polymer modified asphalt are more resistant to tearing and nail pull-out, reducing the risk of shingle blow-off.



THE ZONE[®]: IMPROVE FASTENER PLACEMENT

The Zone[®] nailing area dramatically improves correct fastener placement during installation.







FLEXIBLE IN ALL WEATHER

Polymer modified asphalt technology provides flexibility for application in a wider range of climates and roof styles.



** WIND WARRANTIES

110 mph (177 kph) Limited Wind Warranty included. Eligible for a 130 mph (209 kph) Enhanced Wind Warranty when additional standards are met.



FEATURING

- Limited Lifetime Shingle Warranty
- 15-year Right Start[™] Warranty

TEST COMPLIANCE

- ASTM D7158 Class H
- ASTM D3161 Class F
- ASTM E108 Class A Fire Rating
- CSA A123.5
- ICC-ES AC438
- ASTM D3462
- ASTM D3018 Type I
- UL 2218 Class 4
- ICC Approval – ESR-3150
- FBC Approval – #14809



GREENCIRCLE CERTIFIED MANUFACTURING FACILITY

DISCLAIMER: Sample pieces or photographs of shingles may not accurately represent the true color or variations of color blends that will appear on the roof. Before installation, five or six shingles should be laid out and reviewed for conformity to desired color level. If color levels are unsatisfactory, advise your dealer before proceeding with installation. Colors and specifications subject to change without notice. Shingle colors not available in all regions. Limited warranties carry terms and conditions. Please contact your local Malarkey representative for color availability and further information. See Malarkey's Shingle and Accessory Warranty for details.



Malarkey
Roofing Products[®]
Defining Excellence.[™]

* For complete Limited Lifetime Warranty details, reference Malarkey's Shingle and Accessory Warranty.

* Malarkey hip and ridge shingles (10", 12" RidgeFlex[™] or 8", 10" EZ-Ridge[™] with Scotchgard[™] Protector from 3M) are recommended for all Malarkey field shingles but required with shingles having Scotchgard[™] Protector to receive Malarkey's Limited Lifetime Scotchgard[™] Protector Warranty. Some contractors adapt 3-tab roofing shingles to use as hip and ridge shingles; The Alaskan[®] featuring Scotchgard[™] can be substituted as hip and ridge shingles for both the Scotchgard[™] Protector Warranty and the Algae Resistant System Warranty from Malarkey. The use of Dura-Seal[™] AR as hip and ridge shingles is only allowed when Dura-Seal[™] AR is the field shingle.

** Shingles come with a Limited Wind Warranty but are eligible for an Enhanced Wind Warranty when additional standards are met: Smart Start[™] starter shingles are installed, shingles are 6-nailed (including starter shingles; 9 nails for Windsor[®] shingles), and either EZ-Ridge[™] (8", 10") or RidgeFlex[™] (10", 12") hip and ridge shingles are used. Some contractors adapt roofing shingles to use as hip and ridge shingles. Use of The Alaskan[®] as a hip and ridge shingle will apply toward the Enhanced Wind Warranty. Dura-Seal[™] (Nexgen[™]) shingles used for hip and ridge will qualify toward an Enhanced Wind Warranty only when Dura-Seal[™] (Nexgen[™]) is the field shingle. Malarkey performance-driven underlayments – Arctic Seal[®], Right Start[™] UDL, or SecureStart[™] Plus – are recommended for added system protection. This version supersedes all previous versions. Rev. 7/18

P.O. Box 17217, Portland, OR 97217
503.283.1191 | 800.545.1191 | Fax: 503.289.7644
WWW.MALARKEYROOFING.COM

